

AVERA PRIME CONCRETE

AVREAPRIM CONCRETE is a two-component epoxy primer for concrete surfaces.

DESCRIPTION

❖ Epoxy primer for preparing concrete surfaces before applying polyurea AVREASPRAY 400.

ADVANTAGES

❖ Easy to apply, seals the concrete surface and increases the polyurea adhesion.

PACKING

10 kg per set (A component 7 kg, B component 3 kg)

STORAGE

12 months in original packaging. Keep original drums tightly closed to prevent contamination by humidity. Store in clean and dry place between 10°C and 30°C.

TECHNICAL DATA

Volatile Organic	Compliant with European
Compounds - VOC (g/l)	environmental legislation
Max. humidity of concrete	5%
during application	
Recoating window	min. 3-6 h, max. 24-48 H
depending on	
temperature	
Adhesion to dry concrete	> 434, > 3 (fracture in
(PSI, MPa)	concrete)
Adhesion to wet concrete	>290, > 2 (NBN EN 1542)
(PSI, MPa)	

HOW TO USE IT

- ❖ Mix A and B component thoroughly.
- Apply to clean, dry and correctly repaired concrete with a roller.
- ❖ Wait at least 2-6 hours before spraying the AVREASPRAY, depending on the temperature

SAFETY & PRECAUTION

- Do not breathe dust/fume/gas/mist/vapor/spray
- ❖ In case of improper ventilation wear respiratory protection
- ❖ Wear protective gloves/clothing and eye & face protection
- ❖ If in eyes: Rinse cautiously with water for several minutes, remove contact lenses, if present & easy to do. Continue rinse.
- ❖ If on skin or Hair: Take off immediately all contaminated clothing. Rinse skin with water & shower

